




65592700A



7341251909



SCHUKO socket outlet with hinged cover with enhanced touch protection, with screw-in lift terminals, Berker S.1

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	mat

Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--------------------------------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with screw-in lift terminals

Equipment

With transparent product label holder	no
---------------------------------------	----

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals

Safety

IK protection code against mechanical impacts	02
Enhanced contact protection	according to VDE 0620-1:2021-02
-	Enhanced contact protection

Identification

Main design line	Berker S.1
------------------	------------

Instructions

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
-