
## product sheet 47241606





47241606



SCHUKO socket outlet with hinged c	over with enhanced touch protection	. Berker S.1. anthracite. matt
contonto coontet outlet man imigea o	orer manetalloca toaon proteodor	, Denter off, and hadree, mate

Technical features

Design	according to DIN 4944
Fixing mode	flush-mountin
Main electrical features	
Nominal voltage	250
Rated voltage	250 V A
Frequency	50/60 H
Rated current	16
Electric current	
Rated current	16
Cover, door	
Cover	Central cover plat
Materials	
Colour of design line	anthracit
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black gre
Material	thermoplast
Surface appearance	ma
Installation, mounting	
Installation, mounting Installation mode	for flush-mounted and hollow-wall mountin
-	for flush-mounted and hollow-wall mountin
Installation mode	
Installation mode Connection	according to IEC 60884-
Installation mode Connection Connection terminals	according to IEC 60884-
Installation mode Connection Connection terminals Connection terminals	according to IEC 60884-
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals	according to IEC 60884- according to VDE 0620-1:2021-0
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals Equipment	according to IEC 60884- according to VDE 0620-1:2021-0
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals Equipment With transparent product label holder	according to IEC 60884- according to VDE 0620-1:2021-0 n
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals Equipment With transparent product label holder Use	according to IEC 60884- according to VDE 0620-1:2021-0 n
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals Equipment With transparent product label holder Use Differentiation characteristic 2 - Sales	according to IEC 60884- according to VDE 0620-1:2021-0 n with enhanced touch protectio
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals Equipment With transparent product label holder Use Differentiation characteristic 2 - Sales Safety	for flush-mounted and hollow-wall mountin according to IEC 60884- according to VDE 0620-1:2021-0 n with enhanced touch protectio 0 according to VDE 0620-1:2021-0
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals Equipment With transparent product label holder Use Differentiation characteristic 2 - Sales Safety IK protection code against mecanical impacts	according to IEC 60884- according to VDE 0620-1:2021-0 n with enhanced touch protectio
Installation mode Connection Connection terminals Connection terminals - with plug-in terminals Equipment With transparent product label holder Use Differentiation characteristic 2 - Sales Safety IK protection code against mecanical impacts Enhanced contact protection	according to IEC 60884- according to VDE 0620-1:2021-0 n with enhanced touch protectio



## Instructions

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.