



6765116086



<b>Socket outlet with earthing pin and hinged cover with enhanced touch protection, with lock - differing lockings, with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9</b>	
Technical features	
<b>Architecture</b>	
Fixing mode	flush-mounting
- 2pole + earth	
<b>Main electrical features</b>	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
<b>Cover, door</b>	
Cover	Central cover plate
<b>Materials</b>	
Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety
<b>Installation, mounting</b>	
Installation mode	with spreader claws
<b>Connection</b>	
Connection terminals	according to IEC 60884-1
<b>Use</b>	
Differentiation characteristic 1 - Sales	with enhanced touch protection
Differentiation characteristic 2 - Sales	with lock - differing lockings
Differentiation characteristic 3 - Sales	with screw-in lift terminals
<b>Safety</b>	
IK protection code against mechanical impacts	05
- without enhanced contact protection	
<b>Identification</b>	
Main design line	Berker Q.1/Q.3/Q.7/Q.9
<b>Instructions</b>	
Information text	Spare keys and other closures (max. 24) on request.
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).	