



6768117004



|  |                                |
|--|--------------------------------|
| <b>Socket outlet with earthing pin and hinged cover with enhanced touch protection, with lock - differing lockings, Berker K.5</b> |                                |
| Technical features   |                                |
| <b>Architecture</b>  |                                |
| Fixing mode  | flush-mounting                 |
| - 2pole + earth  |                                |
| <b>Connectivity</b>  |                                |
| Type of USB port   | other                          |
| <b>Main electrical features</b>  |                                |
| Nominal voltage  | 250 V                          |
| Rated voltage  | 250 V AC                       |
| Frequency  | 50/60 Hz                       |
| Rated current  | 16 A                           |
| <b>Cover, door</b>   |                                |
| Cover  | Central cover plate            |
| <b>Materials</b>   |                                |
| Colour of design line  | stainless steel                |
| Colour   | Stainless steel                |
| Colour   | stainless steel optics         |
| RAL colour   | RAL 9022 - Pearl light grey    |
| Material / workmanship   | metal, matt finish             |
| Material   | thermoplastic                  |
| Surface appearance   | matt                           |
| <b>Dimensions</b>  |                                |
| Installation depth, flush-mounted boxes  | 31 mm                          |
| <b>Installation, mounting</b>  |                                |
| Installation mode  | with spreader claws            |
| <b>Connection</b>  |                                |
| Connection terminals   | according to IEC 60884-1       |
| <b>Use</b>   |                                |
| Differentiation characteristic 1 - Sales   | with enhanced touch protection |
| Differentiation characteristic 2 - Sales   | with lock - differing lockings |
| <b>Safety</b>  |                                |
| IK protection code against mechanical impacts  | 05                             |
| - without enhanced contact protection  |                                |
| <b>Identification</b>  |                                |
| Main design line   | Berker K.5                     |

#### Instructions

---

|   |   |
|---|---|
| Information text  | Spare keys and other closures (max. 24) on request. |
| <hr/> <ul style="list-style-type: none"><li>- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.</li></ul> <hr/> |   |