



6768117006



Socket outlet with earthing pin and hinged cover with enhanced touch protection, with lock - differing lockings, Berker K.1

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	mat

Dimensions

Installation depth, flush-mounted boxes	31 mm
---	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
----------------------	--------------------------

Use

Differentiation characteristic 1 - Sales	with enhanced touch protection
Differentiation characteristic 2 - Sales	with lock - differing lockings

Safety

IK protection code against mechanical impacts	05
- without enhanced contact protection	

Identification

Main design line	Berker K.1
------------------	------------

Instructions

Information text	Spare keys and other closures (max. 24) on request.
------------------	---

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
