



47636084



**SCHUKO socket outlet with hinged cover Lock - differing lockings, Berker Q.1/Q.3/Q.7/Q.9, aluminium, matt, lacquered**

Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety

#### Installation, mounting

Installation mode	with clamp/screw fastening
-------------------	----------------------------

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

#### Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
--	---------------------------

#### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	
- with 2 keys	

---

**Identification**

---

Application, usage	Flush-mounted wet-room installation
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

---

**Instructions**

---

Information text Spare keys and other closures (max. 24) on request.

---

- The locks of an article do have identical lockings.  
When ordering several articles those do usually have differing lockings.
  - Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).
-