



47637003



SCHUKO socket outlet with hinged cover Lock - differing lockings, Berker K.5, aluminium, matt, lacquered

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|------------------------|----------------------------|
| Colour of design line | aluminium |
| Colour | aluminium |
| Colour | aluminium optics |
| RAL colour | RAL 9006 - White aluminium |
| Material / workmanship | lacquered |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|---|-------|
| Installation depth, flush-mounted boxes | 31 mm |
|---|-------|

Installation, mounting

| | |
|-------------------|----------------------------|
| Installation mode | with clamp/screw fastening |
|-------------------|----------------------------|

Connection

| | |
|--------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Use

| | |
|--|---------------------------|
| Differentiation characteristic 2 - Sales | Lock - differing lockings |
|--|---------------------------|

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP20 |

- without enhanced contact protection
- with 2 keys

Identification

| | |
|--------------------|-------------------------------------|
| Application, usage | Flush-mounted wet-room installation |
| Main design line | Berker K.5 |

Instructions

| | |
|------------------|---|
| Information text | Spare keys and other closures (max. 24) on request. |
|------------------|---|

- The locks of an article do have identical lockings.
When ordering several articles those do usually have differing lockings.
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).
