



47637009



SCHUKO socket outlet with hinged cover Lock - differing lockings, Berker K.1, polar white glossy

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

Dimensions

Installation depth, flush-mounted boxes	31 mm
---	-------

Installation, mounting

Installation mode	with clamp/screw fastening
-------------------	----------------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
--	---------------------------

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
<ul style="list-style-type: none">- without enhanced contact protection- with 2 keys	

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker K.1

Instructions

Information text	Spare keys and other closures (max. 24) on request.
<ul style="list-style-type: none">- The locks of an article do have identical lockings. When ordering several articles those do usually have differing lockings.- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).	