



7341258982



**SCHUKO socket outlet with hinged cover with enhanced touch protection, with screw-in lift terminals, Berker S.1/B.3/B.7**

#### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour	white
RAL colour	RAL 1013 - Oyster white
Material	thermoplastic
Surface appearance	glossy

#### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw-in lift terminals	

#### Equipment

With transparent product label holder	no
---------------------------------------	----

#### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals

#### Safety

IK protection code against mechanical impacts	02
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

#### Identification

Main design line	Berker S.1/B.3/B.7
------------------	--------------------

#### Instructions

---

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
-