



6768117003



Socket outlet with earthing pin and hinged cover with enhanced touch protection, with lock - differing lockings, Berker K.5, aluminium, matt, lacquered

Technical features

Architecture

| | |
|-----------------|----------------|
| Fixing mode | flush-mounting |
| - 2pole + earth | |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|------------------------|----------------------------|
| Colour of design line | aluminium |
| Colour | aluminium |
| Colour | aluminium optics |
| RAL colour | RAL 9006 - White aluminium |
| Material / workmanship | aluminium, anodised |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|---|-------|
| Installation depth, flush-mounted boxes | 31 mm |
|---|-------|

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|----------------------|--------------------------|
| Connection terminals | according to IEC 60884-1 |
|----------------------|--------------------------|

Use

| | |
|--|--------------------------------|
| Differentiation characteristic 1 - Sales | with enhanced touch protection |
| Differentiation characteristic 2 - Sales | with lock - differing lockings |

Safety

| | |
|---|----|
| IK protection code against mechanical impacts | 05 |
| - without enhanced contact protection | |

Identification

| | |
|------------------|------------|
| Main design line | Berker K.5 |
|------------------|------------|

Instructions

Information text

Spare keys and other closures (max. 24) on request.

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
-