



6768117009



Socket outlet with earthing pin and hinged cover with enhanced touch protection, with lock - differing lockings, Berker K.1, polar white glossy	
Technical features	
Architecture	
Fixing mode	flush-mounting
- 2pole + earth	
Connectivity	
Type of USB port	other
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
Cover, door	
Cover	Central cover plate
Materials	
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy
Dimensions	
Installation depth, flush-mounted boxes	31 mm
Installation, mounting	
Installation mode	with spreader claws
Connection	
Connection terminals	according to IEC 60884-1
Use	
Differentiation characteristic 1 - Sales	with enhanced touch protection
Differentiation characteristic 2 - Sales	with lock - differing lockings
Safety	
IK protection code against mecanical impacts	05
- without enhanced contact protection	
Identification	
Main design line	Berker K.1

Instructions

Information text	Spare keys and other closures (max. 24) on request.
------------------	---

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
