



20298982

Thermostat, change-over heating/cooling switch Berker S.1/B.3/B.7, white glossy

Technical features

Main	ρl	ectric	al te	eatures

Nominal voltage	230 V AC
Frequency	50 Hz

Electric current

Heating switching current	5 A
"Switching current ""Cooling"""	2 A

Measurement

Relative humidity (without condensation)	095 %
Range of temperatures	5 / 30 °C

Materials

Material	Plastic/metal

Installation, mounting

Installation mode	without spreader claws
-------------------	------------------------

Connection

Condu	uctor cross-section (rigid)	12,5 mm²
ط دنید د	h nlug in tarminala	

with plug-in terminals

Equipment

Switching temperature difference	≈ 0.5 K
Switching temperature unreferice	≈ 0,3 K

- setting knob with temperature range limitation
- e.g. for valve drives closed in de-energised state

Safety

Degree of contamination	2
-------------------------	---

Use conditions

Operating temperature	055 °C
Energy efficiency class	I (1%)

- temperature control range adjustable
- Temperature measurement via internal temperature sensor
- with thermal return

Identification

Application, usage	HVAC control
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7