



### 20291909

## Thermostat, change-over heating/cooling switch Berker S.1/B.3/B.7, polar white matt

Technical features

Main	מום	ctric	ol t	_at	IIPAC

Nominal voltage	230 V AC
Frequency	50 Hz

#### **Electric current**

Heating switching current	5 A
"Switching current ""Cooling"""	2 A

## Measurement

Relative humidity (without condensation)	095 %
Range of temperatures	5 / 30 °C

#### Materials

Material	Plastic/metal

### Installation, mounting

Installation mode	without spreader claws
-------------------	------------------------

#### Connection

Conductor cross-section (rigid)	12,5 mm <sup>2</sup>
with plug in terminals	

- with plug-in terminals

### **Equipment**

Switching temperature difference	≈ 0.5 K
owitering temperature unreferred	- 0,0 K

- setting knob with temperature range limitation
- e.g. for valve drives closed in de-energised state

### Safety

Degree of contamination	2
-------------------------	---

### **Use conditions**

Operating temperature	055 °C
Energy efficiency class	I (1%)

- temperature control range adjustable
- Temperature measurement via internal temperature sensor
- with thermal return

# Identification

Application, usage	HVAC control
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7