


2973



Universal rotary dimmer (R, L, C, LED) with soft-lock, Light control

Technical features

Functions

- bulb-preserving soft startup

Controls and indicators

- with soft-lock

Main electrical features

Nominal voltage	230 V
Frequency	50/60 Hz

Voltage

Operating voltage	230 V AC
- voltage test possible without dismantling	

Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

Power

Dimmable conventional transformers	20...210 VA
Loss power at full load	≈ 2 W
Electronic transformers	20...210 W

Materials

Colour	not applicable
Material	Plastic/metal

Dimensions

Insertion depth	24 mm
Axis dimension Ø	4 mm

LED control

Dimmable 230 V retrofit LED lamps	3...60 W
-----------------------------------	----------

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	20...210 W
--	------------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Type of load	Universal and LED Retrofit
Conductor cross-section	0,5...4 mm ²
- with screw terminals	

Scope of delivery

- with incremental encoder

Equipment

- phase cut-on or cut-off according to load type, self-learning
- with brightness memory

Use

Differentiation characteristic 3 - Sales with soft-lock

Identification

Application, usage Light control

Main design line Light control