


29442045



Universal rotary dimmer with centre plate (R, L, C, LED) with soft-lock, Serie R.classic, black glossy

Technical features

Functions

- bulb-preserving soft startup

Controls and indicators

- with soft-lock

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 230 V |
| Frequency | 50/60 Hz |

Voltage

| | |
|---|----------|
| Operating voltage | 230 V AC |
| - voltage test possible without dismantling | |

Fuse

| | |
|------|--|
| Fuse | short-circuit and overload proof (electronic fuse) |
|------|--|

Power

| | |
|------------------------------------|-------------|
| Dimmable conventional transformers | 20...420 VA |
| Loss power at full load | ≈ 4 W |
| Electronic transformers | 20...420 W |

Measurement

| | |
|----------------------|---|
| Extension unit input | with input for extension units insert for universal rotary dimmer, with extension unit input for push-button (NO contact) with single-surface operation |
|----------------------|---|

Materials

| | |
|-----------------------|---------------|
| Colour of design line | black |
| Colour | black |
| Material | Plastic/metal |

Dimensions

| | |
|------------------|-------|
| Insertion depth | 24 mm |
| Axis dimension Ø | 4 mm |

LED control

| | |
|-----------------------------------|-----------|
| Dimmable 230 V retrofit LED lamps | 3...100 W |
|-----------------------------------|-----------|

Incandescent bulbs control

| | |
|--|------------|
| 230 V incandescent lamps and halogen lamps | 20...420 W |
|--|------------|

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|-------------------------|----------------------------|
| Type of load | Universal and LED Retrofit |
| Conductor cross-section | 0,5...4 mm ² |
| - with screw terminals | |

Scope of delivery

- with incremental encoder

Equipment

- phase cut-on, cut-off or LED phase cut-on according to load type, self-learning
- with brightness memory

Use

| | |
|--|----------------|
| Differentiation characteristic 3 - Sales | with soft-lock |
|--|----------------|

Identification

| | |
|--------------------|-----------------|
| Application, usage | Light control |
| Main design line | Serie R.classic |