



90960002



KNX radio/quicklink

Technical features

Functions

Stabilized	yes
Suitable for safety functions	no

Compatibility

Compatible with DIN rail mounting	no
-----------------------------------	----

Main electrical features

Rated operational voltage Ue	100 / 240 V
Rated voltage	100...240 V AC
Frequency	50 Hz

Voltage

Direct out put voltage	5 V
------------------------	-----

Electric current

Ouput intensity	3 A
-----------------	-----

Power

Power consumed	0,3 VA
----------------	--------

Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

Materials

Colour independent of design lines	polar white
Surface appearance	mat

Dimensions

Depth	26,5 mm
Depth of installed product	71,7 mm
Height of installed product	33,25 mm
Width of installed product	50 mm
Height	203 mm
Width	77 mm

Installation, mounting

Direct mounting possible	yes
Suitable for busbar mounting	no
Suitable for front mounting	no

Scope of delivery

Scope of delivery	Power supply included in scope of delivery of the coviva smartbox, with socket outlet adapters for EURO, British, Indian and Australian standard
-------------------	--

Accessories included

Replacement	replacement
-------------	-------------

Equipment

Short-circuit protected	yes
-------------------------	-----

Safety

Protection index IP	IP30
---------------------	------

Use conditions

Operating temperature	0...45 °C
-----------------------	-----------

Identification

Application, usage	KNX radio - system units
--------------------	--------------------------

Main design line	KNX radio/quicklink
------------------	---------------------
