



48031404



**SCHUKO socket outlet with 2 x USB with enhanced touch protection, Berker S.1/B.3/B.7, aluminium, matt, lacquered**

#### Technical features

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Connectivity

Type of USB port	AA
- with 2 USB sockets type A	

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V
Efficiency at low load (10 %)	76,1 %
Average active efficiency	84,7 %
Frequency	50 Hz
Rated current	16 A

#### Voltage

Input voltage	220...250 V AC
Output voltage	4,75...5,25 V DC

#### Electric current

Input current	max. 500 mA
Output current	2,4 A
Output current when operating both sockets	max. 2400 mA
Output current per socket	max. 2400 mA
Rated current	16 A

#### Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	----------------------------------------------------

#### Power

Power consumption (standby)	< 50 mW
Output power	12 W
No-load power consumption	68 mW

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material	Plastic/metal
Surface appearance	matt

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--------------------------------------------

#### Connection

Conductor cross-section (flexible)	1,5...2,5 mm <sup>2</sup>
Conductor cross-section (rigid)	1,5...2,5 mm <sup>2</sup>
- with plug-in terminals	

#### Equipment

With transparent product label holder	no
---------------------------------------	----

#### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
------------------------------------------	--------------------------------

#### Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to VDE 0620-1:2021-02

#### Use conditions

Operating temperature	5...35 °C
-----------------------	-----------

#### Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7