



48038982



**SCHUKO socket outlet with 2 x USB with enhanced touch protection, Berker S.1/B.3/B.7, white glossy**

Technical features

**Architecture**

Fixing mode flush-mounting

**Connectivity**

Type of USB port AA  
- with 2 USB sockets type A

**Main electrical features**

Nominal voltage 250 V  
Rated voltage 250 V  
Efficiency at low load (10 %) 76,1 %  
Average active efficiency 84,7 %  
Frequency 50 Hz  
Rated current 16 A

**Voltage**

Input voltage 220...250 V AC  
Output voltage 4,75...5,25 V DC

**Electric current**

Input current max. 500 mA  
Output current 2,4 A  
Output current when operating both sockets max. 2400 mA  
Output current per socket max. 2400 mA  
Rated current 16 A

**Fuse**

Fuse short-circuit and overload proof (electronic fuse)

**Power**

Power consumption (standby) < 50 mW  
Output power 12 W  
No-load power consumption 68 mW

**Cover, door**

Cover Central cover plate

**Materials**

Colour white  
Colour white  
RAL colour RAL 1013 - Oyster white  
Material Plastic/metal  
Surface appearance glossy

### Dimensions

Insertion depth	32 mm
-----------------	-------

### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

### Connection

Conductor cross-section (flexible)	1,5...2,5 mm <sup>2</sup>
------------------------------------	---------------------------

Conductor cross-section (rigid)	1,5...2,5 mm <sup>2</sup>
---------------------------------	---------------------------

- with plug-in terminals

### Equipment

With transparent product label holder	no
---------------------------------------	----

### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

### Safety

IK protection code against mechanical impacts	02
---	----

Protection index IP	IP20
---------------------	------

Enhanced contact protection	according to VDE 0620-1:2021-02
-----------------------------	---------------------------------

### Use conditions

Operating temperature	5...35 °C
-----------------------	-----------

### Identification

Main design line	Berker S.1/B.3/B.7
------------------	--------------------

Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
--------------------------	------------------------------------