



48031909



SCHUKO socket outlet with 2 x USB with enhanced touch protection, Berker S.1/B.3/B.7, polar white matt

Technical features

Architecture

Fixing mode flush-mounting

Connectivity

Type of USB port AA
- with 2 USB sockets type A

Main electrical features

| | |
|-------------------------------|--------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V |
| Efficiency at low load (10 %) | 76,1 % |
| Average active efficiency | 84,7 % |
| Frequency | 50 Hz |
| Rated current | 16 A |

Voltage

| | |
|----------------|------------------|
| Input voltage | 220...250 V AC |
| Output voltage | 4,75...5,25 V DC |

Electric current

| | |
|--|--------------|
| Input current | max. 500 mA |
| Output current | 2,4 A |
| Output current when operating both sockets | max. 2400 mA |
| Output current per socket | max. 2400 mA |
| Rated current | 16 A |

Fuse

Fuse short-circuit and overload proof (electronic fuse)

Power

| | |
|-----------------------------|---------|
| Power consumption (standby) | < 50 mW |
| Output power | 12 W |
| No-load power consumption | 68 mW |

Cover, door

Cover Central cover plate

Materials

| | |
|--------------------|-----------------------|
| Colour | polarwhite |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | Plastic/metal |
| Surface appearance | matt |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|--|
| Installation mode | for flush-mounted and hollow-wall mounting |
|-------------------|--|

Connection

| | |
|------------------------------------|---------------------------|
| Conductor cross-section (flexible) | 1,5...2,5 mm ² |
| Conductor cross-section (rigid) | 1,5...2,5 mm ² |
| - with plug-in terminals | |

Equipment

| | |
|---------------------------------------|----|
| With transparent product label holder | no |
|---------------------------------------|----|

Use

| | |
|--|--------------------------------|
| Differentiation characteristic 2 - Sales | with enhanced touch protection |
|--|--------------------------------|

Safety

| | |
|---|---------------------------------|
| IK protection code against mechanical impacts | 02 |
| Protection index IP | IP20 |
| Enhanced contact protection | according to VDE 0620-1:2021-02 |

Use conditions

| | |
|-----------------------|-----------|
| Operating temperature | 5...35 °C |
|-----------------------|-----------|

Identification

| | |
|--------------------------|------------------------------------|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |